

**BID NOTICE 2023
TOWN OF EAGLE POINT
CHIPPEWA COUNTY
Hot Oil Chip Sealing and Crack Filling**

The Town of Eagle Point will be accepting sealed bids for the following, Hot Oil-sealing and crack-filling projects for 2023. Refer to attached maps for locations of all roads included in this Bid Notice.

Hot Oil Chip-Sealing (HO)

HO-1	160 th Ave. from 145 th St. to 165 th Ave	2.25 Miles
HO-2	145 th Ave.. from 175 th St. to State Hwy 178	1.00 Mile
HO-3	181 st St. from 145 th St. to end	.15 Miles
HO-4	145 th St. Spur from 145 th St. to 183 rd St.	.10 Miles
HO-5	184 th St. from 183 rd St. to end	.24 Miles
HO-6	183 rd St. from 182 nd St. to State Hwy 178	1.4 Miles
HO-7	187 th St. from 145 th Ave. to end	.10 Miles
HO-8	170 th St. from State Hwy 178 to 120 th Ave.	.43 Miles
HO-9	120 th Ave. from 170 th St. to end	.22 Miles
HO-10	137 th St. from 85 th Ave. to end	.4 Miles
HO-11	85 th Ave. from 136 th St. to end	.2 Miles
HO-12	86 th Ave. from 136 th St. to 185 th Ave.	.2 Miles

This hot oil chip-sealing work shall consist of supplying and placement of a single application of hot oil liquid asphalt seal coat with cover aggregate to the pavement surface. Immediately prior to applying the asphalt material, the existing surface shall be thoroughly cleaned of all loose material, dust, salt, vegetation and other objectionable material. Particular care shall be taken to thoroughly clean the outer pavement edges, ruts, dips and intersections. Pavement and air temperature shall be 60° F or higher. Relative humidity shall be less than 75%. Chip-seal materials shall not be placed during rain or fog or, if rain or is expected, before set time.

Following the application of the hot oil liquid asphalt, a cover aggregate consisting of 3/8" minus fractured chips shall be applied uniformly over the asphalt material. The aggregate shall be immediately rolled with pneumatic tire rollers until thoroughly embedded in the asphalt material.

Contractor shall be responsible for removing loose excess chips where necessary.

Traffic control shall be provided by the contractor to maintain safety, minimize distress to the fresh asphalt seal coat and allow access to property during construction and curing. Contractor shall provide all flagging.

Crack-Filling (CF)

CF-1	185 th St. from 145 th Ave. to new blacktop	1.00 Mile
CF-2	190 th St. from 192 nd St. north to end	.13 Miles
CF-3	120 th Ave. from State Hwy 178 to end	.18 Miles
CF-4	155 th St. from County Hwy Y including 135 th Ave. and 160 th St. ending at 125 th Ave.	2.00 Miles
CF-5	120 th Ave. from State Hwy 124 to 150 th St. to 115 th Ave. to 152 nd St. to 110 th Ave. end at State Hwy 178	2.75 Miles
CF-6	150 th St. from County Hwy S to end	.50 Miles
CF-7	139 th St. from 95 th Ave. to 96 th Ave. to 136 th St. end at 95 th Ave.	.3 Miles

The work shall consist of furnishing all materials, equipment and labor for cleaning and sealing of transverse and longitudinal joints in asphalt pavement unless otherwise noted.

Route cracks to a minimum of $\frac{3}{4}$ x $\frac{3}{4}$ inch ratio width versus depth. Blow and clean cracks with compressed air and heat lance. Seal crack with poly fiber crack sealant which exceeds ASTM-6690 TYPE II sealant. One inch overband on all cracks. Repair all failed or open cracks previously filled.

For **wider and cupped cracks (cupped depth greater than $\frac{1}{2}$ " and width greater than 3")**, blow out and clean cracks with compressed air and heat lance. Flood area with poly-fiber material meeting ASTM-6690 and cover immediately with 1/8" coated aggregate. For wider and cupped cracks, blow out and clean cracks with compressed air and heat lance. Flood area with poly-fiber material meeting ASTM-6690 and cover immediately with either uncoated or coated 1/8" washed chips, fractured pea gravel not-to-exceed 3/8" or similar material. Aggregate to be applied to entire flooded area by covering fully and embedding with a roller or using compressed air to inject material into the asphalt material.

Traffic control shall be provided by the contractor to maintain safety and allow access to property during construction. Contractor shall provide all flagging.

Pre-Bid Road Inspections

Bidders are responsible for confirming dimensions and existing conditions of roads included in the Ad for Bid. For more information, contact Jesse Zwiefelhofer, Town Road Crew Lead, at (715) 828-2487.

Bid Documents

Bids are to be signed and must be submitted on a Town of Eagle Point Bid Form which is available from Laurie Hebert, Town Clerk, 14802 State Highway 124, Chippewa Falls, WI 54729 or by email at townofeaglepoint@gmail.com. Bids must be submitted to the Eagle Point Town Hall by 7:00 pm on Monday, May 15, 2023 at which time they will be opened and read aloud and awarded. Prior to contract award, the successful bidder must provide a Certificate of Insurance.

The Town of Eagle Point reserves the right to waive irregularities and accept or reject any and all bids.

Laurie Hebert, Clerk
Town of Eagle Point
14082 State Highway 124
Chippewa Falls, WI 54729
